



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitsuoi.co.jp

quality.always

MJ-214. MITASU ULTRA CJ-4/SN 15W-40 100% Synthetic

MITASU ULTRA CJ-4/SN 15W-40 100% Synthetic is motor oil formulated to meet the latest OEM (Original Equipment Manufacturer) requirements. Synthetic base combined with a blend of premium additives ensure extended service interval and outstanding performance and safety for automobiles with diesel engines manufactured by Japanese, European and the United States carmakers.

APPLICATION

MITASU ULTRA CJ-4/SN 15W-40 100% Synthetic is designed for modern heavy-duty and high-speed turbocharged or non-turbocharged diesel engines of long-distance UHPD (Ultra High Performance Diesel) class vehicles, running in under severe duty operating conditions, equipped with exhaust gas after-treatment systems (EURO V) and the previous ones, including vehicles fitted with diesel particulate filters (DPF) and/or three-way catalysts. Recommended for all-season use.

SPECIFICATIONS / APPROVALS

- API CJ-4/SN
- ACEA E7/E9-08
- CATERPILLAR ECF-1A/ECF-2/ECF-3
- CUMMINS CES 20071/20081
- DETROIT DIESEL 93K215/93K218
- MACK EO-O PP07
- MAN 3275
- MERCEDES-BENZ 228.31
- RENAULT RLD-3
- VOLVO VDS-4



APPLICATION BENEFITS

MITASU ULTRA CJ-4/SN 15W-40 100% Synthetic provides:

- Provides the level of quality specified by OEM (Original Equipment Manufacturer)
- Extends oil drain interval
- Maximum thermal stability
- Longer life of after treatment systems as CAT and DPF
- Minimizes oil consumption through burning
- Provides protection from oxidation
- Keeps engine free from slugs and harmful deposits

MITASU ULTRA CJ-4/SN 15W-40 100% Synthetic meets requirements of the following manufactures of heavy-duty diesel machinery: TOYOTA, NISSAN, MITSUBISHI, MAZDA, ISUZU, HYUNDAI, KIA, FORD, DAF, IVECO, MAN, MACK, RENAULT, VOLVO, MERCEDES-BENZ, CATERPILLAR, CUMMINS and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	15W-40
Density at 15°C	ASTM D-4052	0,8715
Flash point, °C	ASTM D-92	230
TBN (mg KOH/g)	ASTM D-2896	9,50
Pour point, °C	ASTM D-97	-36
Colour	ASTM D-1500	4,0
Viscosity index	ASTM D-2270	146
Kinematic viscosity at 40°C (cSt)	ASTM D-445	101,70
Kinematic viscosity at 100°C (cSt)	ASTM D-445	14,50

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2014 Mitsuo Oil Corporation, Japan.

1L

4L

6L

20L

200L

